



## LM13 4x4 Multi-Purpose Security Vehicle

- **High Protected High Mobility Law Enforcement Vehicle.**
- **400 hp Diesel engine coupled to a 6 speed automatic gearbox.**
- **Independent suspension with integrated CTIS and ABS.**
- **Landmine protection STANAG 4569 (Certified).**
- **Ballistic protection STANAG 4569 (Certified).**
- **IED Protection (Certified).**
- **Can be fitted with a variety of riot control equipment.**
- **The LM13 can be deployed for Special Weapons and Tactics (SWAT).**



Website: [www.ott-armor.com](http://www.ott-armor.com); Email: [sales@ott-armor.com](mailto:sales@ott-armor.com)

# BASIC SPECIFICATIONS

## LM13 4x4 Multi-Purpose Security Vehicle



Specifications are subject to change without prior notice

### ENGINE

#### Cummins 400

Type	Cummins 400 hp 8.8 litre in-line 6 cylinder turbo diesel engine with intercooler
Max Power	1627 Nm; 298 kW
Fuel Type	Diesel

### TRANSMISSION

Type	Fully automatic 6 speed with 2 speed transfer case
No of gears	6

### SUSPENSION

Type	Axletech independent suspension
------	---------------------------------

### WHEELS AND TIRES

Wheels & Tires	365/80 R20 Michelin XZL (spare wheel included)
CTIS	Fully automatic as standard with 4 terrain settings and 3 load settings

Run Flat	Fitted as standard. Can drive 50 km at 50 km/h
----------	--

### CONFIGURATION

Seating: Total crew	2 (driver, commander) and 8 rear dismounts.
Entrance doors	1 x left side door, 1 x right side door, double rear doors, 2 x roof hatches and 1 x turret hatch

### STANDARD FITMENT

Air conditioner	13 kW AC with front and rear vents.
Winch	Standard 8 t with 22 m cable.
Fire suppression	Manually activated for engine compartment, wheels and inside vehicle. In addition 2 x hand held fire extinguishers inside vehicle.

### DIMENSIONS

Overall length	6.68 m (Incl spare wheel & dozer) 6.12 m (Incl spare wheel Excl dozer)
Overall width	2.85 m (Incl Mirrors) 2.50 m (Excl Mirrors)
Overall height	2.77 m (To top of Turret)
Ground clearance (min)	400 mm (Below differential)
Fording	1000 mm unprepared
Fuel capacity	300 litres

### VEHICLE MASS

Gross vehicle mass (GVM)	13 000 kg
--------------------------	-----------

### PERFORMANCE

Max speed	120 km/h (Electronically limited)
Max gradient	70 %
Vertical step	400 mm
Dynamic side slope	40 %

### PROTECTION

The V-shape monocoque hull protects the crew against rifle fire, anti-tank mines and IED's.

