




PUMA M26 - 155 4x4 Mine Protected Vehicle (MPV)

- **Robust, reliable and proven drive line**
- **Excellent road and rough terrain mobility**
- **Low maintenance costs**
- **Multi-role capabilities**
- **Comprehensive product support**



Website: www.ott-armor.com; Email: sales@ott-armor.com

BASIC SPECIFICATIONS

PUMA M26 - 155 4x4 Mine Protected Vehicle (MPV)



Specifications are subject to change without prior notice

ENGINE

| | |
|---------------|----------------------------|
| Type | Cummins B5.9-155-30 |
| Configuration | In line 6 cylinder turbo |
| Displacement | 5 883 cc |
| Max Power | 115 kW (155 hp) @ 2500 rpm |
| Max Torque | 590 Nm @ 1500 rpm |
| Fuel Type | Diesel |

TRANSMISSION

| | |
|-------------|----------------------|
| Type | G600 synchromesh |
| No of gears | 6 Forward. 1 Reverse |

TRANSFER CASE

| | |
|------|------------------------|
| Type | 2-speed selectable 4x4 |
|------|------------------------|

STEERING

| | |
|----------------------------|--------------------------------------|
| Type | Hydraulic power assisted |
| Steering wheel orientation | Right hand drive, Left hand optional |

BRAKES

| | |
|-----------------|-------------------------------|
| Service brakes | Dual air system |
| Park brake | Spring operated on both axles |
| Auxiliary brake | Engine exhaust brake |

SUSPENSION

| | |
|-----------------|------------------------------------|
| Springs | Semi elliptic leaf springs |
| Shock absorbers | Double acting telescopic hydraulic |

WHEEL AND TIRES

| | |
|------------------|---|
| Wheels & tires | Rims: 8.00 x 20 Tires: 12.00 x 20 - 18 Ply Rating |
| Run Flat Inserts | Optional |

CONFIGURATION

| | |
|---------------------|--|
| Seating: Total Crew | Up to 10 (APC) |
| Variants | APC, tactical command, patrol vehicle (6 crew) |
| Entrance doors | One main door plus 2 side doors in drivers compartment |

STANDARD FITMENT

| | |
|-----------------|--|
| Air conditioner | Yes |
| Defence ports | 9 in crew compartment + 2 in drivers compartment |
| Seat belts | Fitted to all seats |

ELECTRICAL SYSTEM

24 Volt

DIMENSIONS

| | |
|------------------------|----------|
| Overall length | 5 810 mm |
| Overall width | 2 265 mm |
| Overall height | 2 710 mm |
| Ground clearance (min) | 300 mm |
| Fuel capacity | 200 L |

VEHICLE MASS DATA

| | |
|--------------------------|----------|
| Tare mass | 7 200 kg |
| Gross vehicle mass (GVM) | 8 130 kg |
| Payload | 930 kg |

PERFORMANCE

| | |
|----------------------|-------------------|
| Max. speed | 100 km/h |
| Sustained road speed | 80 km/h |
| Fuel autonomy | > 800 km on roads |
| Max. gradient | 60% |

PROTECTION

The V-shape monocoque hull protects the crew against rifle fire, anti-tank mines and IED's.

Errors and omissions excluded



UMT, LLC

4228 Lomac Street, Montgomery, Alabama, 36106

Website: www.ott-armor.com; Email: sales@ott-armor.com

PUMA M26 Iss:2022